

ACO Euroline			
Product Picture	ACO Description	Article No.	List Price
Euroline 55			
	Supply of Prefab Polymer Concrete Euroline Channels in accordance to DIN EN 1433 with following properties. a) Compressive strength -96 N/mm2 b) Flexural strength -27 N/mm2 c) Water absorption - 0.07% d) Mannings roughness- 0.011. The Channels will be 'V'-profile in shape with screw less locking grating, without slope. The Channels interlocking shall be with tongue and groove joints and are with anchoring features on the outside wall to ensure mechanical bond to the surrounding bedding material and pavement surface. The channels will be with knock-out preform for connection to 110mm pipe, provided with inbuilt bottom outlet suitable for DN 100 and with all range of accessories like end plate / end plate with outlet suitable for DN 60. The Channel gratings will be made up of Stainless Steel 304 in 500 mm / 1000 mm length suitable as per load class A-15 / B-125 / C-250 conforming to EN 1433. The Channels nominal width will be 98 mm with overall width 118 mm and invert depth of the drain 55 mm as per design. Dimensions : 1000x118x55 (LxWxH), Height (55 mm). Art. No: 810000	810000	2850
ACO Euroline 97			
	Supply of Prefab Polymer Concrete Euroline Channels in accordance to DIN EN 1433 with following properties. a) Compressive strength -96 N/mm2 b) Flexural strength -27 N/mm2 c) Water absorption - 0.07% d) Mannings roughness- 0.011. The Channels will be 'V'-profile in shape with screw less locking grating, without slope. The Channels interlocking shall be with tongue and groove joints and are with anchoring features on the outside wall to ensure mechanical bond to the surrounding bedding material and pavement surface. The Channels will be with knock-out preform for connection to 110mm pipe, provided with inbuilt bottom outlet suitable for DN 100 and with all range of accessories like end plate / end plate with outlet suitable for DN 100. The Channel gratings will be made up of Stainless Steel 304 in 500 mm / 1000 mm length suitable as per load class A-15 / B-125 / C-250 conforming to EN 1433. The Channels nominal width will be 98 mm with overall 118 mm and invert depth of the drain 97 mm as per design. Dimensions : 1000x118x97 (LxWxH); Height (97, mm). Art. No: 38500	38500	3450
ACO Euroline 139			
	Supply of Prefab Polymer Concrete Euroline Channels in accordance to DIN EN 1433 with following properties. a) Compressive strength -96 N/mm2 b) Flexural strength -27 N/mm2 c) Water absorption - 0.07% d) Mannings roughness- 0.011. The Channels will be 'V'-profile in shape with screw less locking grating, without slope. The Channels interlocking shall be with tongue and groove joints and are with anchoring features on the outside wall to ensure mechanical bond to the surrounding bedding material and pavement surface. The Channels will be with knock-out preform for connection to 110mm pipe, provided with inbuilt bottom outlet suitable for DN 100 and with all range of accessories like end plate / end plate with outlet suitable for DN 100. The Channel gratings will be made up of Stainless Steel 304 in 500 mm / 1000 mm length suitable as per load class A-15 conforming to EN 1433. The Channels nominal width will be 98 mm with overall 118 mm and invert depth of the drain 139 mm as per design. Dimensions : 1000x118x139 (LxWxH); Height (139, mm). Art. No: 810008	810008	5350
ACO Euroline Grating			
	Double slot SS grating with slot opening of 6 mm pickle passivated having ht. 16 mm for pedestrain load class. Art. No: 155011	155011	5850
	Single slot grating with discreet inlet slot size of 10 mm i.e. intake area of 100 cm2/m with Ht. 25 mm and 1000 mm in length, made of Stainless Steel 1.50 mm thick 304 grade material certified to pedestrain load class and with fully removable maintenance unit. Art. No: 155065	155065	10600
	Single Wave / Dual Wave design with anti-slip protection with snap fit locking, of wt. 2.9 kg for load class B-125/C-250 certified as per EN 1433. Art. No: 155061/155060	155060	8250
	Ductile Iron grating with drainlock having slotted bar type design with anti- slip protection with snap fit locking, of wt. 2.9 kg for load class B-125/C- 250 certified as per EN 1433. Art. No: 155058	155058	3350
Channel Accessories			
	Aco Euroline H-25 Single Slot Inspection Unit (200mm)	155066	6400
	Brick Single slot grating with Ht. 25 mm and 800 mm in length.	155067	9500
	Aco Euroline 55 End Cap	810200	900
	Aco Euroline 55 End Cap With Outlet	810201	1550
	Aco Euroline 55 vertical Outlet (knockout)	810020	4380
	Aco Euroline 97 End Cap	38504	990
	Aco Euroline 97 End Cap With Outlet	38505	1860

	Aco Euroline 97 vertical Outlet (knockout)	810024	6900
	Aco Euroline 139 End Cap	810202	590
	Aco Euroline 139 End Cap With Outlet	810203	2700
	Pradhan Plumbing System	810028	8600